

Nozzles >>

DETERGENT NOZZLE



1/4BSPM

FIG 13


HIGH PRESSURE NOZZLE



1/4BSPM

FIG 14

NOZZLE HOLDER



1/4BSPF x 1/4BSPF

FIG 8

NOZZLE HOLDER



1/4BSPF x 1/4BSPF

FIG 8A

Code	Nozzle Size	Standard Angle	Optional Angles				Pressure		Inlet	Weight g	pcs
							bar	psi			
FIG 13	Detergent	N/A	N/A					350	1/4 BSPM	17	1
FIG 14	030	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14A	035	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14B	040	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14C	045	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14D	050	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14E	055	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14F	060	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14G	065	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14H	070	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14I	075	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14J	080	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14K	085	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14L	090	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14M	095	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14N	100	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14O	105	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14P	110	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14Q	115	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14R	120	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14S	125	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14T	130	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14U	135	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14V	140	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	
FIG 14W	145	15°	0°	25°	40°	350	5000	1/4 BSPM	17	1	

Code	Weight g	Flow LPM	Rated Temperature		Pressure		Inlet	Outlet	pcs
					bar	psi			
FIG 8	179	N/A	150°C	300°F	350	350	1/4 BSPF	1/4 BSPF	1
FIG 8A	179	15°	150°C	300°F	350	5000	1/4 BSPF	1/4 BSPF	1

* All Nozzles are rated to 150°C / 300°F

Please Note:

A drop in PSI performance on your pressure cleaner can be attributed to the nozzle simply being worn out. Pumps Australia recommend replacing your nozzle every 100hours of use or so.

These nozzles can be used at High Pressures with Higher wear rates

- To order nozzles, please specify the degree you require

Example: FIG14-15° or FIG 14-25°