

## Swivels (3000 - 10,000PSI) >>

MATERIAL: BRASS

BRASS 3200PSI  
3/8x3/8" MF  
COMPACT




FIG 22A

BRASS 4000PSI  
3/8x3/8" MF



FIG 22

HD BRASS 4650PSI  
3/8x3/8" MF  
CONTRACTOR



FIG 22-HD

HD BRASS 5075PSI  
3/8x3/8" MF



FIG 22-SHD

RECOMMENDED

MATERIAL: STAINLESS STEEL

STAINLESS STEEL  
3200PSI  
3/8x3/8" MF



FIG 22SS

STAINLESS STEEL  
5800PSI  
1/4x1/4" MF



FIG 23

STAINLESS STEEL  
5070PSI  
3/8x3/8" MF



FIG 23A

STAINLESS STEEL  
8700PSI  
1/2x1/2" MF



FIG 23B

USED IN UHP APPLICATIONS!



STAINLESS STEEL 90°  
1/4x1/4" MF



FIG 124

STAINLESS STEEL 90°  
3/8x3/8" MF



FIG 124A

STAINLESS 90°  
1/2x3/8" MF



Suits:  
FIG 37B - 50ft  
FIG 37C - 100ft

FIG 124B

BRASS 90° ELBOW  
3/8x3/8" MF



Suits:  
FIG 37D - 150ft  
FIG 37E - 200ft

FIG 124C

BRASS 90° ELBOW  
1/2x3/8" MF



Suits:  
FIG 37B - 50ft  
FIG 37C - 100ft

FIG 124D

HOSE REEL

HOSE REEL

HOSE REEL

Code	Flow LPM	Rated Temperature		Pressure		Inlet	Outlet	Weight g	pcs	
				bar	psi					
FIG 22A	40	150°C	300°F	220	3200	3/8 BSPM	3/8 BSPF	102	1	
FIG 22	40	150°C	300°F	280	4000	3/8 BSPM	3/8 BSPF	102	1	
FIG 22-HD	40	150°C	300°F	320	4650	3/8 BSPM	3/8 BSPF	123	1	
FIG 22-SHD	40	150°C	300°F	390	5070	3/8 BSPM	3/8 BSPF	123	1	
FIG 22SS	40	150°C	300°F	220	3200	3/8 BSPM	3/8 BSPF	90	1	
FIG 23	40	150°C	300°F	399	5800	1/4 BSPM	1/4 BSPF	168	1	
FIG 23A	40	150°C	300°F	390	5070	3/8 BSPM	3/8 BSPF	168	1	
FIG 23B	60	150°C	300°F	600	8700	1/2 BSPM	1/2 BSPF	405	1	
<b>90° ELBOW SWIVEL</b>										
FIG 124	40	150°C	300°F	280	4000	1/4 BSPM	1/4 BSPF	180	1	
FIG 124A	40	150°C	300°F	280	4000	3/8 BSPM	3/8 BSPF	195	1	
FIG 124B	45	150°C	300°F	350	5000	1/2 BSPM	3/8 BSPF	437	1	
FIG 124C	45	150°C	300°F	350	5000	3/8 BSPM	3/8 BSPF	200	1	
FIG 124D	45	150°C	300°F	350	5000	1/2 BSPM	3/8 BSPF	300	1	