



## Rotary Floor Cleaners (Water Recovery) >>

### Contractor Series (Stainless Steel)

#### Features:

- All 304SS vacuum system ensure the long turn use and anti-erosion by high speed water jetting along with debris. Max suck for 2.5m height and delivery 15m length.
- Industrial grade swivel build with tungsten seats and 304SS bearings, allows a long run use for non-maintenance.
- Unit comes with 5m length PU water delivery tube, can be connect max up to 15m(not include).



FIG 65 WR

Code	Max Flow (LPM)	Rated Temperature		Pressure		Inlet	Outlet	Weight KG	pcs
				bar	psi				
FIG 65 WR-15	30	90°C	200°F	280	4060	3/8 Ball M	2x Nozzle	14	1
FIG 65 WR-18	30	90°C	200°F	280	4060	3/8 Ball M	2x Nozzle	15	1
FIG 65 WR-21	30	90°C	200°F	280	4060	3/8 Ball M	2x Nozzle	16	1
FIG 65 WR-24	30	90°C	200°F	280	4060	3/8 Ball M	2x Nozzle	17	1

### High Pressure Cleaner & Water Recover in One-Step

The Water Recovery Surface Cleaner makes high pressure cleaning and water recovery in ONE-STEP, it automatic sucks the dirty water along with the debris (smaller than 4mm) through the venturi system and delivery into a drain or recycle tank.

Integrated venturi sucking system eliminate the use of a Vacuum Cleaner, it sucks the dirty water away from the asphalt, concrete, marble, tile and other flat surface and leaves like the rag wipe over, that makes the surface cleaning job more efficient both for indoor and outdoor usage.

When the venturi system utilize hydro jet to create the vacuum it will reduce the cleaning force, so a greater flow pressure washer is recommended.

